



### INFORMATION

- + Zero Halogen
- + Flame Retardent
- + Low Smoke Generation At Burnings
- + Meets DEF Stan 59-97 Issue 3, Type 8
- + Print on liner enabled
- + Easy Pick Application
- + Print performance to military requirements
- + Perforation between each marker for easy tear

### SPECIFICATIONS

**Temperature range**

-40°C to +105°C

**Material**

cross linked UV stabilised and printable polyolefin

**Print**

thermal transfer

**Print performance**

Adherence: SAE-AS81531-1998 Clause 4.6.2

Fluid Resistance: MIL202 Method 215J

**Standard colours**

yellow and white

**Shrink ratio**

2:1

**Certified and issued to:**

Meets DEF STAN 59-97, issue 3 Type 8  
LUL Standard 1-085 (Limited, Dispersed usage)  
(Formerly LUL 2-01001-002)  
BS6853 - Vehicle Cat. 1a

## DIMENSIONS | PACKAGING

TYPE	DIAMETER (D mm)	DIAMETER (D1 mm)	SLEEVE LENGTH (mm)	MARKERS ACCROSS	MARKERS / BOX
EF^024125LR*	2.4	0.8	12.5	4	4000
EF^024250LR*	2.4	0.8	25	2	2000
EF^024500LR*	2.4	0.8	50	1	1000
EF^032125LR*	3.2	1.10	12.5	4	4000
EF^032250LR*	3.2	1.10	25	2	2000
EF^032500LR*	3.2	1.10	50	1	1000
EF^048125LR*	4.8	1.6	12.5	4	4000
EF^048250LR*	4.8	1.6	25	2	2000
EF^048500LR*	4.8	1.6	50	1	1000
EF^064125LR*	6.4	2.10	12.5	4	4000
EF^064250LR*	6.4	2.10	25	2	2000
EF^064500LR*	6.4	2.10	50	1	1000
EF^095125LR*	9.5	3.2	12.5	4	2000
EF^095250LR*	9.5	3.2	25	2	1000
EF^095500LR*	9.5	3.2	50	1	500
EF^127125LR*	12.7	4.2	12.5	4	2000
EF^127250LR*	12.7	4.2	25	2	1000
EF^127500LR*	12.7	4.2	50	1	500
EF^190125LR*	19.0	6.4	12.5	4	2000
EF^190250LR*	19.0	6.4	25	2	1000
EF^190500LR*	19.0	6.4	50	1	500
EF^254250LR*	25.4	8.5	12.5	4	600
EF^254500LR*	25.4	8.5	25	2	300
EF^381500LR*	25.4	8.5	50	1	100

^ = S (single sided), D (double sided)

\* = Colour (4=Yellow, 9=White)